REMI Healthcare

Portable Tube Sealer
WeldOn-P

WeldOn-P

REMI portable sealer **WeldOn-P** is a battery operated tube sealer. **WeldOn-P** comes with portable sealing handle and long Coaxial Cable (1.9m) for extended reach especially for handling sealing requirements in blood donation room & outdoor camps.

High performance rechargeable battery ensures a capacity for 1000 seals with a single charge.

Seal with clear break line for snap-apart separation

Salient Features

- Ergonomic hand-held design to ensure easy sealing process.
- Quick sealing by single lever press process
- LED indicator for **Power, Battery** & **Sealing Process**.
- Anti-spark and overheat protection system to avoid damage to tubing.
- Consistent sealing process with clear break line for snap-apart separation.
- Battery backup for 1000 seals.
- Removable cover for easy cleaning & protection of the operator.
- No warm-up time required.
- Sealing process works on both mains & battery power.
- Audio-visual indication of:
  - Ready to Seal
  - Sealing in Process
  - Sealing Completed

Technical Specifications

Parameters	WeldOn-P
Dimension (W x D x H) (mm)	124 x 222 x 123
Weight (Kg)	2.5kg (with Sealing Handle)
RF Frequency	40.68 MHZ
RF Output	90 watt
Seal Time	3 Sec (Adjustable)
Sealing Type	Manual

Input Voltage: 230V, 50 Hz

Specifications subject to change without notice

REMI Healthcare

Benchtop Tube Sealer
WeldOn-B

WeldOn-B

Splash Gaurd

WeldOn-B is a robust benchtop sealer with consistent performance. Ideally suited for blood component separation labs

WeldOn-B helps to keep the blood bag system completely sterile. Ensures quality sealing with clear rupture line for easy tear-apart segments.

Safety features & monitoring system makes it an ideal choice of users.

Seal with clear break line for snap-apart separation

Salient Features

- Senses the blood bag tube for automatic sealing process
- Anti-spark and overheat protection system to avoid damage to system & tubing
- Continuous status updates on LCD :
  - Ready to seal,
  - Sealing in process
  - Sealing Completed
- Easy to remove sealing head cap for quick cleaning
- Seal with clear break line for snap-apart separation
- Splash guard for technician safety
- LED Indication for cover opening

Technical Specifications	
Parameters	**WeldOn-B**
Dimension (W x D x H) (mm)	220 x 200 x 120
Weight (Kg)	4
RF Frequency	40.68 MHZ
RF Output	100 watt
Seal Time	1.5 Sec (auto adjustable)
Sealing Type	Automatic

Input Voltage: 230V, 50 Hz

Specifications subject to change without notice